

## Down Light

LED 8-12-16 W

### CTL-DL-8-AC



Light Source	1x8 W High Power Korea LED
Lamp Total Power	>8 W
Luminous Flux	790 Lm
Color Temperature	3000 K / 5000 K
Beam Angle	120°
Input Voltage	110 - 240 V AC
Frequency	50 Hz
Working Environment	-30° C ... 50° C
Lamp Body	Aluminum Die Casting
Working Lifetime	40000 Hours
Color Rendering Index	Ra >80
IP Rating	IP 50
Weight	700 Gr
Dimension	H : 70 mm, D : 150 mm

### CTL-DL-12-AC



Light Source	1x12 W High Power Korea LED
Lamp Total Power	>12 W
Luminous Flux	1200 Lm
Color Temperature	3000 K / 5000 K
Beam Angle	120°
Input Voltage	110 - 240 V AC
Frequency	50 Hz
Working Environment	-30° C ... 50° C
Lamp Body	Aluminum Die Casting
Working Lifetime	40000 Hours
Color Rendering Index	Ra >80
IP Rating	IP 50
Weight	700 Gr
Dimension	H : 70 mm, D : 150 mm

### CTL-DL-16-AC



Light Source	1x16 W High Power Korea LED
Lamp Total Power	>16 W
Luminous Flux	1600 Lm
Color Temperature	3000 K / 5000 K
Beam Angle	120°
Input Voltage	110 - 240 V AC
Frequency	50 Hz
Working Environment	-30° C ... 50° C
Color Rendering Index	Ra >80
Lamp Body	Aluminum Die Casting
Working Lifetime	40000 Hours
IP Rating	IP 50
Weight	1200 Gr
Dimension	H : 90 mm, D : 200 mm